



ORION 4-20

Type	4-20
System	Three-phase
Input voltage variation	± 20 %
Rated power	4 kVA
Input voltage range	320-480 V
Max input current	7.3 A
Output voltage	400 V
Rated output current	5.8 A
Efficiency	>96 %
Compensation Duration	Continuous
Adjustment speed	12 ms/V
Dimensions WxDxH	410x530x1200mm
Weight	90 kg



This image is indicative only.

Standard features

Voltage stabilisation	Independent phase control
Selectable output voltage	220-230-240V (L-N) / 380-400-415V (L-L)
Frequency	50Hz ± 5 % or 60Hz ± 5 %
Output voltage accuracy	$\pm 0,5$ %
Admitted load variation	Up to 100%
Admitted load imbalance	100 %
Cooling	Up to 45kVA ± 15 % natural ventilation From 60kVA ± 15 % aided with fans
Ambient temperature	-25/+45°C
Storage temperature	-25/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	200% 2min.
Harmonic distortion	None introduced
Colour	RAL 7035
Protection degree	IP 21
Instrumentation	Output digital multimeter
Installation	Indoor
Overvoltage protection	Output class II surge arrestors (over 60kVA ± 15 %)

Optional Accessories

Interrupting devices - INPUT	DI 10 - INPUT
Interrupting devices - OUTPUT	DI 10 - OUTPUT
Load protection against over/undervoltage	PS 10
CAM	CAM25
Input three-phase isolation transformer DYN11	DYN11 17A
SPD Surge arrestors	SPD INPUT CLASS I 25/4
SPD Surge arrestors	SPD OUTPUT CLASS II 20/4