



ORION 20-15

Type	20-15
System	Three-phase
Input voltage variation	±15 %
Rated power	20 kVA
Input voltage range	340-460 V
Max input current	34 A
Output voltage	400 V
Rated output current	29 A
Efficiency	>98 %
Compensation Duration	Continuous
Adjustment speed	16 ms/V
Dimensions WxDxH	410x680x1200mm
Weight	155 kg



This image is indicative only.

Standard features

Voltage stabilisation	Independent phase control
Selectable output voltage	220-230-240V (L-N) / 380-400-415V (L-L)
Frequency	50Hz ±5% or 60Hz ±5%
Output voltage accuracy	±0,5%
Admitted load variation	Up to 100%
Admitted load imbalance	100 %
Cooling	Up to 45kVA ±15% natural ventilation From 60kVA ±15% aided with fans
Ambient temperature	-25/+45°C
Storage temperature	-25/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	200% 2min.
Harmonic distortion	None introduced
Colour	RAL 7035
Protection degree	IP 21
Instrumentation	Output digital multimeter
Installation	Indoor
Overvoltage protection	Output class II surge arrestors (over 60kVA ±15%)

Optional Accessories

Interrupting devices - INPUT	DI 40 - INPUT
Interrupting devices - OUTPUT	DI 32 - OUTPUT
Load protection against over/undervoltage	PS 32
CAM	CAM40
Input three-phase isolation transformer DYN11	DYN11 36A
SPD Surge arrestors	SPD INPUT CLASS I 25/4
SPD Surge arrestors	SPD OUTPUT CLASS II 20/4