



VEGA 4-15/35

Type	4-15/35
System	Single-phase
Input voltage variation	+15/-35 %
Rated power	4 kVA
Input voltage range	150-265 V
Max input current	27 A
Output voltage	230 V
Rated output current	17 A
Efficiency	>98 %
Compensation Duration	Continuous
Adjustment speed	10 ms/V
Dimensions WxDxH	300x560x300mm
Weight	42 kg



This image is indicative only.

Standard features

Selectable output voltage	220-230-240V (dip switch)
Frequency	50Hz $\pm$ 5% or 60Hz $\pm$ 5%
Output voltage accuracy	$\pm$ 0,5%
Admitted load variation	Up to 100%
Cooling	Natural ventilation
Ambient temperature	-25/+45°C
Storage temperature	-25/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	200% 2min.
Harmonic distortion	None introduced
Colour	RAL 7035
Protection degree	IP 21
Instrumentation	Output digital voltmeter
Installation	Indoor

Optional Accessories

Interrupting devices - INPUT	DI 32 - INPUT
Interrupting devices - OUTPUT	DI 20 - OUTPUT
Load protection against over/undervoltage	PS 20
CAM	CAM25
Single-phase input isolation transformer	34A
SPD Surge arrestors	SPD INPUT CLASS I 25/2
SPD Surge arrestors	SPD OUTPUT CLASS II 20/2