



## VEGA 10-15/35

|                         |                |
|-------------------------|----------------|
| Type                    | 10-15/35       |
| System                  | Single-phase   |
| Input voltage variation | +15/-35 %      |
| Rated power             | 10 kVA         |
| Input voltage range     | 150-265 V      |
| Max input current       | 67 A           |
| Output voltage          | 230 V          |
| Rated output current    | 43 A           |
| Efficiency              | >98 %          |
| Compensation Duration   | Continuous     |
| Adjustment speed        | 10 ms/V        |
| Dimensions WxDxH        | 410x530x1200mm |
| Weight                  | 125 kg         |



*This image is indicative only.*

### Standard features

|                           |                                  |
|---------------------------|----------------------------------|
| Selectable output voltage | 220-230-240V (dip switch)        |
| Frequency                 | 50Hz $\pm 5\%$ or 60Hz $\pm 5\%$ |
| Output voltage accuracy   | $\pm 0,5\%$                      |
| Admitted load variation   | Up to 100%                       |
| Cooling                   | Natural ventilation              |
| Ambient temperature       | -25/+45°C                        |
| Storage temperature       | -25/+60°C                        |
| Max relative humidity     | <95% (non condensing)            |
| Admitted overload         | 200% 2min.                       |
| Harmonic distortion       | None introduced                  |
| Colour                    | RAL 7035                         |
| Protection degree         | IP 21                            |
| Instrumentation           | Output digital voltmeter         |
| Installation              | Indoor                           |

### Optional Accessories

|                                           |                          |
|-------------------------------------------|--------------------------|
| Interrupting devices - INPUT              | DI 80 - INPUT            |
| Interrupting devices - OUTPUT             | DI 50 - OUTPUT           |
| Load protection against over/undervoltage | PS 50                    |
| CAM                                       | CAM63                    |
| Single-phase input isolation transformer  | 86A                      |
| SPD Surge arrestors                       | SPD INPUT CLASS I 25/2   |
| SPD Surge arrestors                       | SPD OUTPUT CLASS II 20/2 |