



ODYSSEY 400-20

Type	400-20
System	Three-phase
Input voltage variation	±20 %
Rated power	400 kVA
Input voltage range	320-480 V
Max input current	722 A
Output voltage	400 V
Rated output current	577 A
Efficiency	>98 %
Compensation Duration	Continuous
Adjustment speed	<3 ms
Dimensions WxDxH	1200x1000x2200mm
Weight	1200 kg



This image is indicative only.

Standard features

Voltage regulation	IGBT control (double conversion technology)
Voltage stabilisation	Independent phase control
Selectable output voltage	220-230-240V (L-N) / 380-400-415V (L-L)
Frequency	50Hz ±5% or 60Hz ±5%
Output voltage accuracy	±0,5%
Admitted load variation	Up to 100%
Admitted load imbalance	100 %
Cooling	Forced ventilation
Ambient temperature	0/+40°C
Storage temperature	0/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	110% continuous, 120% for 60s, >120% automatic by-pass protection
Colour	RAL 9005
Protection degree	IP 2X
Instrumentation	10" touch panel, multilingual (on request remotely available by dedicated software connected to the same Ethernet network)
Installation	Indoor
Communication system	MODBUS TCP/IP
Overvoltage protection	Class I input surge arrestors Class II output surge arrestors
Protections	Automatic by-pass protection

Optional Accessories

Interrupting devices - INPUT	DI 800 - INPUT
Interrupting devices - OUTPUT	DI 630 - OUTPUT
Load protection against over/undervoltage	PS 630
Automatic circuit breaker and changeover switch	IA-CA 800
Input three-phase isolation transformer DZN0	DZN0 722A



Integrated PFC automatic systems from 400kVA to 800kVA	PFC 400-800 400
Total protection kit	TPK 800
EMI/RFI filters	FL 800