



ODYSSEY 4000-15

Type	4000-15
System	Three-phase
Input voltage variation	±15 %
Rated power	4000 kVA
Input voltage range	340-460 V
Max input current	6793 A
Output voltage	400 V
Rated output current	5774 A
Efficiency	>98 %
Compensation Duration	Continuous
Adjustment speed	<3 ms
Dimensions WxDxH	4200x1400x2200mm
Weight	5900 kg



This image is indicative only.

Standard features

Voltage regulation	IGBT control (double conversion technology)
Voltage stabilisation	Independent phase control
Selectable output voltage	220-230-240V (L-N) / 380-400-415V (L-L)
Frequency	50Hz ±5% or 60Hz ±5%
Output voltage accuracy	±0,5%
Admitted load variation	Up to 100%
Admitted load imbalance	100 %
Cooling	Forced ventilation
Ambient temperature	0/+40°C
Storage temperature	0/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	110% continuous, 120% for 60s, >120% automatic by-pass protection
Colour	RAL 9005
Protection degree	IP 2X
Instrumentation	10" touch panel, multilingual (on request remotely available by dedicated software connected to the same Ethernet network)
Installation	Indoor
Communication system	MODBUS TCP/IP
Overvoltage protection	Class I input surge arrestors Class II output surge arrestors
Protections	Automatic by-pass protection

Optional Accessories